



Refinish Paints

DULAC THINNER

SAFETY PRECAUTIONS:

STORAGE:

Store in a cool, dry, well ventilated place and keep container lightly closed. Store in accordance with national regulations for Flammable or Highly Flammable liquids. For flash points below 23 degrees Celsius store in accordance with the Highly Flammable Liquids and Liquefied Petroleum Gas Regulations 1972.

HANDLING:

Avoid contact with the skin and eyes. Smoking, eating and drinking should be prohibited in the work area. Wear suitable gloves for protection against materials. Wear suitable eye protection. Wear appropriate protective clothing. Barrier creams may help to protect exposed areas of skin but are not a substitute for full physical protection. Do not allow materials of this kind to enter drains. Dispose of treated waste as directed by the relevant waste disposal authorities.

FLAMMABILITY:

Dulac Thinner is highly flammable material. All sources of ignition must be eliminated in, or near the working place. Fight fire with foam, CO₂, dry chemical powder. DO NOT SMOKE.

EMERGENCY TREATMENT:

EYES:

Irrigate copiously with clean, fresh water for at least 10 minutes, holding eyelids apart. Seek medical advice.

SKIN:

Remove contaminated clothing, wash skin thoroughly with soap and water, or use a proprietary skin cleanser. Do not use solvents or thinners. Seek medical advice if Symptoms persist

INHALATION:

Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume the most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

INGESTION:

If accidentally swallowed, DO NOT INDUCE VOMITING. Keep at rest and obtain medical attention.

All information contained in this Data Sheet is as accurate and up-to-date as possible. Products can be expected to perform as indicated in this sheet, so long as applications and application procedures are recommended. However there are no expressed or implied warranties.



Refinish Paints

DULAC THINNER

USES: For thinning of (NC based) paints, Primers, Clear Lacquers, Top Coat Colours.

TYPICAL PROPERTIES AND APPLICATION DATA:			
COMPOSITION:	A mixture of Aliphatic and Aromatic Hydro-Carbons, Esters and Ketones	SPECIFIC GRAVITY:	0.79 ± 0.02
COLOUR:	Water White		
FLASH POINT:	Below 23°C		